






CIXI WANJIE ELECTRONIC CO., LTD

THE SPEC SHEET



Electrical

Standard	UL	IEC
Rated voltage	150V	130V
Rated current	2A	6A
Contact resistance	20mΩ	
Insulation resistance	500MΩ/DC500V	
Wrth standing voltage	AC1300V/1 Min	
Wire range	26~20AWG	0.5mm ²

Mechanical

Temp.Range	-40°C~+105°C
MAX Soldering	+250°C for 5 Sec
Steip Length	11mm

Dimensions

Pitch	2.54mm
Poles	1-XXP

Material

Housing	PA66, UL94V-0
Pin header	Brass, Tin plated
Wire guard	Stainless steel

linear dimension(Tolerances Standard GB/T 14486-2008)												≡	—	□	//	⊥
variable range	to 6	over 6 to 10	over 10 to 18	over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 200	over 200 to 250	over 250 to	all	to 5	over 5 to 30	over 30 to 120	over 120 to
tolerance	±0.1	±0.14	±0.19	±0.25	±0.32	±0.43	±0.57	±0.72	±0.88	±1.05	±1.25	0.5	0.025	0.06	0.12	0.4

UNITS	mm	SIZE	A4	SCALE	2.3:1	THIRD ANGLE PROJECTION	
CIXI WANJIE ELECTRONIC CO., LTD						TITLE	WJ141V-2.54-XXP-1YY-00A