


CIXI WANJIE ELECTRONIC CO., LTD

THE SPEC SHEET



P.C.B. LAYOUT

Electrical

Standard	UL	IEC
Rated voltage	300V	320V
Rated current	15A	13.5A
Contact resistance	20mΩ	
Insulation resistance	500MΩ/DC500V	
Wrth standing voltage	AC 2000V/1 Min	

Mechanical




Temp.Range	-40°C~+105°C
MAX Soldering	+250°C, for 5 Sec

Dimensions

Pitch	5.08mm
Poles	2~24p

Material

Housing	PA66, UL94V-0
Clamp	Copper alloy, Sn plated



linear dimension(Tolerances Standard GB/T 14486-2008)

		over 6 to 10	over 10 to 18	over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 200	over 200 to 250	all		over 5 to 30	over 30 to 120	over 120 to
variable range	to 6														
tolerance	±0.1	±0.14	±0.19	±0.25	±0.32	±0.45	±0.57	±0.72	±0.88	±1.05	±1.25	0.5	0.025	0.06	0.12

UNITS	mm	SIZE	A4	SCALE	3:1	THIRD ANGLE PROJECTION	
						TITLE	WJ2EDGB-5.08-XXP-1YY-00A