






CIXI WANJIE ELECTRONIC CO., LTD


THE SPEC SHEET




08~24P



02~03P



04~07P



Electrical

Standard	UL	IEC
Rated voltage	300V	450V
Rated current	15A	20A
Contact resistance	20mΩ	
Insulation resistance	500MΩ/DC500V	
Wire range	22~14AWG	2.5mm ²
Wrth standing voltage	AC 2000V/1 Min	

Mechanical

Torque	0.5Nm(4.5Lb.in)
Steip Length	7-8mm
Temp.Range	-40°C~+105°C

Dimensions

Pitch	5mm
Poles	02~24p

Material

Housing	PA66, UL94V-0
Screws	M3 Steel, Zn plated
Clamp	Phosphor bronze, Ni plated
Cage	Brass ,Ni plated

linear dimension(Tolerances Standard GB/T 14486-2008)												≡	—	□	//	⊥
variable range	to 6	over 6 to 10	over 10 to 18	over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 200	over 200 to 250	over 250 to	all	to 5	over 5 to 30	over 30 to 120	over 120 to
tolerance	±0.1	±0.14	±0.19	±0.25	±0.32	±0.43	±0.57	±0.72	±0.88	±1.05	±1.25	0.5	0.025	0.06	0.12	0.4

UNITS	mm	SIZE	A4	SCALE	2:1	THIRD ANGLE PROJECTION	
						TITLE	WJ2EDGKZ-5.0-XXP-1YY-00A
CIXI WANJIE ELECTRONIC CO., LTD							